

- 90° milling angle
- Cylindrical shank
- 5% cobalt HSS
- Head with 3 cutting edges



Countersinking bits Ø 10.4 - 16.5 - 20.5 - 25 - 31 mm Plastic case



#### Machine



#### Application



**K**  
K- Ferrous  
Cast iron  
with Short  
Chips

**M1**  
M1-  
austenitic  
stainless  
steels

**N**  
N- Non-  
ferrous  
alloys

**P1**  
P1-  
Unrealized  
steels

**P2**  
P2-  
Weakly  
allied  
steels

#### Features



#### Properties and benefits

- + 90° milling angle : For 90° chamfering operation. ➡ For making 90° chamfering to down screw and/or rivet heads.
- + Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. ➡ Enables versatile use on portable electrical tools and CNC machine tools.
- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➡ For general use in metals up to 1200 N/mm².
- + Head with 3 cutting edges: tool geometry designed with 3 cutting edges. ➡ Enables the excellent distribution of the cutting force and a neat surface condition.

#### Données de gestion :

PCB : 1 / Kilogram. : 0,294 / Dimensions : 0110x0075x0075 mm / EAN : 3221910628178