

1036132 | DIN335C HSSE5% cobalt 90° deburring cutter with hole - Cylindrical shank

Fast and long-lasting deburring bit for high-strength steels and stainless steels.





- Especially for stainless steel and high-strength steels
- Superior long life
- **Excellent surface finish**
- Gradual work
- Cylindrical shank
- 5% cobalt HSS



Machine

Application





















K- Ferrous Cast iron with Short Chips

M1austenitic stainless steels

N- Nonferrous alloys

P1-Unrealized steels

Weak allied steels

Features















Properties and benefits

- + Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. Enables versatile use on portable electrical tools and
- → 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) → For general use in metals up to 1200 N/mm².



Item number M3	EAN (13 digits) M3	Cutter diameter	Handle diameter or CM	Drill diameter d3	Total length	Trimmed length	Quantity No. pieces per sales unit	PCB By How Much M3
10361320205	3221910222871	2-5	6		45	25	1	1
10361320510	3221910222888	5-10	8		48	25	1	1
10361321015	3221910222895	10-15	10		65	35	1	1
10361321520	3221910222901	15-20	12		85	41	1	1