

1036132 | DIN335C HSSE5% cobalt 90° deburring cutter with hole - Cylindrical shank

Fast and long-lasting deburring bit for high-strength steels and stainless steels.




- Especially for stainless steel and high-strength steels
- Superior long life
- Excellent surface finish
- Gradual work

- Cylindrical shank
- 5% cobalt HSS



Machine



Application


M	N 1.4	N 2	P
M- Stainless steels	N1-4-based alloy Aluminum-4000 Series: With Silicon	N2- Magnesium alloy	P- Ferrous Long Chip Steels

Features



Properties and benefits

- + Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. ➡ Enables versatile use on portable electrical tools and CNC machine tools.
- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➡ For general use in metals up to 1200 N/mm².



Item number M3	EAN (13 digits)	M3 Cutter diameter	Handle diameter or CM	Drill diameter d3	Total length	Trimmed leng
10361320205	3221910222871	2-5	6		45	25
10361320510	3221910222888	5-10	8		48	25
10361321015	3221910222895	10-15	10		65	35
10361321520	3221910222901	15-20	12		85	41