

A hand-held reamer that accurately calibrates a cylindrical hole (bore) made with a drill bit. The listel on the outside diameter polishes the bore. For through holes.



- Versatile use
- High-speed steel

Machine



Application

N 1.4	N 2	P 1	P 2	P 3
N1-4-based alloy Aluminum-4000 Series: With Silicon	N2- Magnesium alloy	P1- Unrealized steels	P2- Weakly allied steels	P3- strong alloy steels

Features



Properties and benefits

+ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²



Code	EAN	Ø	d2	L	I	I3	QTY	PCB
10400210200	3221910639532	2	2	50	25		1	1
10400210250	3221910639549	2,5	2.5	58	29		1	1
10400210300	3221910639556	3	3	62	31		1	1
10400210350	3221910639563	3,5	3.5	70	35		1	1
10400210400	3221910639570	4	4	76	338		1	1
10400210450	3221910639587	4,5	4.5	81	41		1	1
10400210500	3221910639594	5	5	87	44		1	1
10400210550	3221910639600	5,5	5.5	93	47		1	1
10400210600	3221910639617	6	6	93	47		1	1
10400210650	3221910639624	6,5	6.5	100	50		1	1
10400210700	3221910639631	7	7	107	54		1	1
10400210750	3221910639648	7,5	7.5	107	54		1	1
10400210800	3221910639655	8	8	115	58		1	1
10400210850	3221910639662	8,5	8.5	115	58		1	1
10400210900	3221910639679	9	9	124	62		1	1
10400210950	3221910639686	9,5	9.5	124	62		1	1
10400211000	3221910639693	10	10	133	66		1	1
10400211100	3221910639709	11	11	142	71		1	1
10400211200	3221910639716	12	12	152	76		1	1
10400211300	3221910639723	13	13	152	76		1	1
10400211400	3221910639730	14	14	163	81		1	1
10400211500	3221910639747	15	15	163	81		1	1
10400211600	3221910639754	16	16	175	87		1	1
10400211700	3221910639761	17	17	175	87		1	1

A hand-held reamer that accurately calibrates a cylindrical hole (bore) made with a drill bit. The listel on the outside diameter polishes the bore. For through holes.

10400211800	3221910639778	18	18	188	93	1	1
10400211900	3221910639785	19	19	188	93	1	1
10400212000	3221910639792	20	20	201	100	1	1
10400212100	3221910639808	21	21	201	100	1	1
10400212200	3221910639815	22	22	215	107	1	1
10400212300	3221910639822	23	23	215	107	1	1
10400212400	3221910639839	24	24	231	115	1	1
10400212500	3221910639846	25	25	231	115	1	1
10400212600	3221910639853	26	26	231	115	1	1
10400212700	3221910639860	27	27	247	124	1	1
10400212800	3221910639877	28	28	247	124	1	1
10400212900	3221910639884	29	29	247	124	1	1
10400213000	3221910639891	30	30	247	124	1	1
10400213100	3221910639907	31	31	265	133	1	1
10400213200	3221910639914	32	32	265	133	1	1