

# 1050294 | Standard tapping/cutter bit HSS -M -TivolyNorm -Straight entry -Hexagonal shank

3 in 1 tool, drill, thread tap and deburring device in one. Suitable for working with steel using a screwdriver or bit holders. 6.35 hexagonal shank



- Especially for soft steels and plastics
- 3 in 1 tool
- Drilling, tapping and milling
- Especially for the Shock Series
  
- Quick-change shank
- High-speed steel

## Machine



## Application



## Features



## Properties and benefits

- + Quick-Change hex attachment: a hexagonal recessed attachment for the quick locking and unlocking of the bit. Compliant with the DIN 3126 E6.3 standard → Enables the quick changing of your bits by doing away with the manual tightening/loosening of the chuck. For drills and screwdrivers.
- + High-speed steel: HSS substrate → For general use in steels and cast irons up to 950 N/mm<sup>2</sup>

Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
1050294030050	3221910881597	M 3	3	0.5	TivolyNorm	2,50	36				1	1
1050294040070	3221910881993	M 4	4	0.7	TivolyNorm	3,30	39				1	1
1050294050080	3221910882006	M 5	5	0.8	TivolyNorm	4,20	41				1	1
1050294060100	3221910881627	M 6	6	1	TivolyNorm	5,00	44				1	1
1050294080125	3221910881634	M 8	8	1.25	TivolyNorm	6,80	49				1	1
1050294100150	3221910881641	M 10	10	1.5	TivolyNorm	8,50	52				1	1