

Multi-application threading. Precision comfort



- Especially for steels and aluminiums
- Comfort and precision

- High-speed steel

Machine



Application

N	P 1	P 2.4
N- Non-ferrous alloys	P1- Unrealized steels	P2-4- Weakly alloyed dechlorage steels

Features

HSS	BRIGHT UNCOATED	EN 24231	BSP G	30-90	CLASS A
------------	------------------------	-----------------	--------------	--------------	----------------

Properties and benefits

+ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²



Item number M3	EAN (13 digits)	M3	Tap or thread diameter	Pitch in mm or TPI	Cage diameter	Cage height	Quantity No.
11004910108	3221910713393		1/8"	28	30	11	
11004910104	3221910713386		1/4"	19	38	10	
11004910308	3221910713416		3/8"	19	45	14	
11004910102	3221910713379		1/2"	14	45	14	
11004910508	3221910713423		5/8"	14	55	16	
11004910304	3221910713409		3/4"	14	55	16	
11004910708	3221910713430		7/8"	14	65	18	
11004911000	3221910713447		1"	11	65	18	
11004911104	3221910713461		1 1/4"	11	75	20	
11004911102	3221910713454		1 1/2"	11	90	22	