

Multi-application threading. Precision comfort



- Especially for steels and aluminiums
- Comfort and precision

- High-speed steel

Machine



Application

N	P 1	P 2.4
N- Non-ferrous alloys	P1- Unrealized steels	P2-4- Weakly alloyed declotage steels

Features

HSS	BRIGHT UNCOATED	EN 24231	BSW	20-55	MEDIUM CLASS
------------	------------------------	-----------------	------------	--------------	---------------------

Properties and benefits

+ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²



Item number M3	EAN (13 digits)	M3	Tap or thread diameter	Pitch in mm or TPI	Cage diameter	Cage height	Quantity No.
11005010108	3221910713492		1/8"	40	20	5	
11005010532	3221910713553		5/32"	32	20	5	
11005010316	3221910713522		3/16"	24	20	7	
11005010104	3221910713485		1/4"	20	20	7	
11005010516	3221910713546		5/16"	18	25	9	
11005010308	3221910713515		3/8"	16	30	11	
11005010716	3221910713577		7/16"	14	30	11	
11005010102	3221910713478		1/2"	12	38	14	
11005010508	3221910713539		5/8"	11	45	18	
11005010304	3221910713508		3/4"	10	45	18	
11005010708	3221910713560		7/8"	9	55	22	
11005011000	3221910713584		1"	8	55	22	