

11400170015 | 19 fully ground HSS metal drill bits Ø 1 to 10 mm by 1/2 TECHNIC

- Especially for high-strength steels and cast irons
- Precise drilling
- Tough
- Versatile use
- Made in France



- Cylindrical shank
- 30° type N flute
- High-speed steel
- 118° tip



Ø 1 - 1.5 - 2 - 2.5 - 3 - 3.5 - 4 - 4.5 - 5 - 5.5 - 6 - 6.5 - 7 - 7.5 - 8 - 8.5 -9 - 9.5 - 10 mm TIVOLY BOX Case



Machine Application 2 1 P2-Weakly allied steels P1-Unrealized steels K2- Gray Cast iron M1austenitic stainless steels Features **DIN** 338 **h**8 HSS 3xd **Properties and benefits** + Conventional grinding: with a standard point sharpening Simple and robust, for versatile use. Enables good hole precision and wear

- resistance.
 Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. Senables versatile use on portable electrical tools and CNC machine tools.
- + 30° type N flute: normal flute profile with a 30° helix angle. Suitable for general use. Provides good rigidity to the tool, as well as excellent drilling precision.
- High-speed steel: HSS substrate Sor general use in steels and cast irons up to 950 N/mm²
- 118° tip: 118° tip angle for the sharpening of the drill bit. Suitable for general use in materials with long shavings. Enables the rapid attach of the material and simple centring.

Données de gestion :

PCB: 1 / Kilogram.: 0,540 / Dimensions: 0180x0140x0043 mm / EAN: 3221912016416