

# 1142091 | Fully ground HSS metal drill bit -STEAM treatment -NFE66075 -h8 -10xd -Extra long L315 mm -Conventional point

High performance drill (10xØ) for versatile and deep drilling due to its geometry and substrate. (Total length: 315). Made in France.




- Especially for high-strength steels, stainless steels and cast irons
- Deep drilling
- Precise drilling
- Tough
- Made in France
- Conventional point
- Cylindrical shank
- 30° type N flute
- High-speed steel
- 118° tip

## Machine



## Application



## Features



## Properties and benefits

- + Conventional grinding: with a standard point sharpening ➡ Simple and robust, for versatile use. Enables good hole precision and wear resistance.
- + Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. ➡ Enables versatile use on portable electrical tools and CNC machine tools.
- + 30° type N flute: normal flute profile with a 30° helix angle. ➡ Suitable for general use. Provides good rigidity to the tool, as well as excellent drilling precision.
- + High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm<sup>2</sup>
- + 118° tip: 118° tip angle for the sharpening of the drill bit. ➡ Suitable for general use in materials with long shavings. Enables the rapid attack of the material and simple centring.



Code	EAN	Ø	d2/CM	L	l	lu	QTY	PCB
11420910400	3221910845421	4	4	315	235		1	1
11420910500	3221910845445	5	5	315	235		1	1
11420910600	3221910845469	6	6	315	235		1	1
11420910800	3221910845506	8	8	315	235		1	1
11420911000	3221910845544	10	10	315	235		1	1
11420911200	3221910845582	12	12	315	235		1	1