

1142101 | Fully ground HSS metal drill bit -STEAM treatment -NFE66075 -h8 -10xd -Extra long L400 mm -Conventional point

High performance drill (10xØ) for versatile and deep drilling due to its geometry and substrate. (Total length: 400). Made in France.



- Especially for high-strength steels and cast irons
- Deep and through-drilling
- Precise drilling
- Tough
- Made in France

- Conventional point
- Cylindrical shank
- 30° type N flute
- High-speed steel
- 118° tip

Machine



Application



Features



Properties and benefits

- + Conventional grinding: with a standard point sharpening ➡ Simple and robust, for versatile use. Enables good hole precision and wear resistance.
- + Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. ➡ Enables versatile use on portable electrical tools and CNC machine tools.
- + 30° type N flute: normal flute profile with a 30° helix angle. ➡ Suitable for general use. Provides good rigidity to the tool, as well as excellent drilling precision.
- + High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²
- + 118° tip: 118° tip angle for the sharpening of the drill bit. ➡ Suitable for general use in materials with long shavings. Enables the rapid attach of the material and simple centring.



Code	EAN	Ø	d2/CM	L	I	lu	QTY	PCB
11421010500	3221910845612	5	5	400	300		1	1
11421010550	3221910845629	5.5	5.5	400	300		1	1
11421010600	3221910845636	6	6	400	300		1	1
11421010650	3221910845643	6.5	6.5	400	300		1	1
11421010700	3221910845650	7	7	400	300		1	1
11421010750	3221910845667	7.5	7.5	400	300		1	1
11421010800	3221910845674	8	8	400	300		1	1
11421010850	3221910845681	8.5	8.5	400	300		1	1
11421010900	3221910845698	9	9	400	300		1	1
11421010950	3221910845704	9.5	9.5	400	300		1	1
11421011000	3221910845711	10	10	400	300		1	1
11421011050	3221910845728	10.5	10.5	400	300		1	1
11421011100	3221910845735	11	11	400	300		1	1



1142101 | Fully ground HSS metal drill bit -STEAM treatment -NFE66075 -h8 -10xd -Extra long L400 mm -Conventional point

High performance drill (10xØ) for versatile and deep drilling due to its geometry and substrate. (Total length: 400). Made in France.

11421011150	3221910845742	11.5	11.5	400	300	1	1
11421011200	3221910845759	12	12	400	300	1	1
11421011250	3221910845766	12.5	12.5	400	300	1	1
11421011300	3221910845773	13	13	400	300	1	1