

1143741 | Fully ground HSS metal drill bit -DIN1897 -h8 -Special sharpening for metal sheet

Drilling and blunting of steel and stainless steel sheets.




- Especially for sheet metal and tubing
- Ultra-precise drilling
- Rapid drilling
- Tough
- Made in France

- Sheet metal cutting
- Cylindrical shank
- 30° type N flute
- High-speed steel

Machine



Application



Features



Properties and benefits

- + Sheet metal cutting: with centring tip and lip. ➡ Circular and burr-free drilling of thin sheet metals. Suitable for the misalignment of weld points.
- + Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. ➡ Enables versatile use on portable electrical tools and CNC machine tools.
- + 30° type N flute: normal flute profile with a 30° helix angle. ➡ Suitable for general use. Provides good rigidity to the tool, as well as excellent drilling precision.
- + High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²



| Code | EAN | Ø | d2/CM | L | I | lu | QTY | PCB |
|-------------|---------------|-----|-------|----|----|----|-----|-----|
| 11437410300 | 3221910213640 | 3 | 3 | 46 | 16 | | 1 | 10 |
| 11437410350 | 3221910213664 | 3.5 | 3.5 | 52 | 20 | | 1 | 10 |
| 11437410400 | 3221910213671 | 4 | 4 | 55 | 22 | | 1 | 10 |
| 11437410420 | 3221910213688 | 4.2 | 4.2 | 55 | 22 | | 1 | 10 |
| 11437410450 | 3221910213695 | 4.5 | 4.5 | 58 | 24 | | 1 | 10 |
| 11437410500 | 3221910213701 | 5 | 5 | 62 | 26 | | 1 | 10 |
| 11437410550 | 3221910213725 | 5.5 | 5.5 | 66 | 28 | | 1 | 10 |
| 11437410600 | 3221910213732 | 6 | 6 | 66 | 28 | | 1 | 10 |
| 11437410800 | 3221910213749 | 8 | 8 | 79 | 37 | | 1 | 10 |
| 11437411000 | 3221910213756 | 10 | 10 | 89 | 43 | | 1 | 5 |