

**1143741 | Fully ground HSS metal drill bit -DIN1897 -h8**  
**-Special sharpening for metal sheet**

Drilling and blunting of steel and stainless steel sheets.



- Especially for sheet metal and tubing
- Ultra-precise drilling
- Rapid drilling
- Tough
- Made in France

- Cylindrical shank
- 30° type N flute
- High-speed steel
- Sheet metal cutting

**Machine**



**Application**



**Features**



**Properties and benefits**

- + Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. ➡ Enables versatile use on portable electrical tools and CNC machine tools.
- + 30° type N flute: normal flute profile with a 30° helix angle. ➡ Suitable for general use. Provides good rigidity to the tool, as well as excellent drilling precision.
- + High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm<sup>2</sup>
- + Sheet metal cutting: with centring tip and lip. ➡ Circular and burr-free drilling of thin sheet metals. Suitable for the misalignment of weld points.



Code	EAN	Ø	d2/CM	L	l	lu	QTY	PCB
11437410300	3221910213640	3	3	46	16		1	10
11437410350	3221910213664	3.5	3.5	52	20		1	10
11437410400	3221910213671	4	4	55	22		1	10
11437410420	3221910213688	4.2	4.2	55	22		1	10
11437410450	3221910213695	4.5	4.5	58	24		1	10
11437410500	3221910213701	5	5	62	26		1	10
11437410550	3221910213725	5.5	5.5	66	28		1	10
11437410600	3221910213732	6	6	66	28		1	10
11437410800	3221910213749	8	8	79	37		1	10
11437411000	3221910213756	10	10	89	43		1	5