

Tap for steel. Passing tail.




- Threading of standard Steels
- Spiral flute
- 5% cobalt HSS

**Machine**



**Application**



**Features**



**Properties and benefits**

- + Spiral flute : A flute shape that allows chips to be evacuated through the entrance to the hole. ➡ Allows better heat resistance due to better chip evacuation. For blind holes.
- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➡ For general use in metals up to 1200 N/mm<sup>2</sup>.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
160355101200175	3221912006097	M 12	1,75	DIN 376	10,25	110	16	2-2.5	7,00	1	1	
160355101400200	3221912006110	M 14	2	DIN 376	12,00	110	18	2-2.5	9,00	1	1	
160355101600200	3221912006127	M 16	2	DIN 376	14,00	110	18	2-2.5	9,00	1	1	
160355101800250	3221912006134	M 18	2,5	DIN 376	15,50	125	25	2-2.5	11,00	1	1	
160355102000250	3221912006141	M 20	2,5	DIN 376	17,50	140	25	2-2.5	12,00	1	1	
160355102400300	3221912006158	M 24	3	DIN 376	21,00	160	30	2-2.5	14,50	1	1	
160355102700300	3221912006165	M 27	3	DIN 376	24,00	160	30	2-2.5	16,00	1	1	
160355103000350	3221912006172	M 30	3,5	DIN 376	26,50	180	35	2-2.5	18,00	1	1	
160355103300350	3221912006189	M 33	3,5	DIN 376	26,50	180	40	2-2.5	20,00	1	1	
160355101200150	3221912006080	MF 12	1,5	DIN 374	10,50	100	14	2-2.5	7,00	1	1	
160355101400150	3221912006103	MF 14	1.5	DIN 374	12,50	100	18	2-2.5	9,00	1	1	