


8036221 | Finishing end mill HSS-E8 (cobalt 8%) -HIGHCUT coated -DIN844BK -Z3-6 -Hel. 40° - Normal

High performance HSS-E8 slot milling cutter which gives the tool a compromise between flexibility and hardness. Versatile use. Made in France.



- Versatile use
- Superior long life
- Made in France

- 8% cobalt HSS
- HIGHCUT coating

Machine



Application



Features



Properties and benefits

- + 8% cobalt high-speed steel : HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness). ↻ For general use in metals up to 1400 N/mm²;
- + HIGHCUT coating : Thickness 2/4µm, hardness 3200 HV, coefficient of friction 0,2, resistance to heat (400°C). ↻ High toughness. Low coefficient of friction. High wear resistance. Only for steels.



Item number	M3	EAN (13 digits)	M3	Cutter diameter	Handle diameter or CM	Total length	Trimmed length	Number of teeth
80362210200		3221910632472		2	6	51	7	
80362210300		3221910632489		3	6	52	8	
80362210400		3221910632496		4	6	55	11	
80362210600		3221910632519		6	6	57	13	
80362210800		3221910632526		8	10	69	19	
80362211000		3221910632533		10	10	72	22	
80362211200		3221910632540		12	12	83	26	
80362211400		3221910632557		14	12	83	26	
80362211600		3221910632564		16	16	92	32	
80362211800		3221910632571		18	16	92	32	
80362212000		3221910632588		20	20	104	38	