

60° drill for centring. Form A.



■ High-speed steel

**Machine**



**Application**



**Features**



**Properties and benefits**

⊕ High-speed steel: HSS substrate ⊕ For general use in steels and cast irons up to 950 N/mm<sup>2</sup>



Code	EAN	Ø	d2/CM	L	lu	QTY	PCB
8140811050315	3221910479763	0.5	3.15	25		1	1
8140811063315	3221910479770	0.63	3.15	25		1	1
8140811080315	3221910479794	0.8	3.15	25		1	1
8140811100315	3221910479831	1	3.15	31		1	1
8140811125315	3221910479893	1.25	3.15	31		1	1
8140811100400	3221910479848	1	4	35		1	1
8140811160400	3221910479923	1.6	4	35		1	1
8140811150500	3221910479916	1.5	5	40		1	1
8140811200500	3221910479947	2	5	40		1	1
8140811200600	3221910479954	2	6	45		1	1
8140811250630	3221910479978	2.5	6.3	45		1	1
8140811250800	3221910480004	2.5	8	50		1	1
8140811300800	3221910480035	3	8	50		1	1
8140811315800	3221910480042	3.15	8	50		1	1
8140811300100	3221910480011	3	10	55		1	1
8140811400100	3221910480059	4	10	55		1	1
8140811400120	3221910480103	4	12	63		1	1
8140811500120	3221910480189	5	12	63		1	1
8140811500125	3221910480202	5	12.5	63		1	1
8140811500140	3221910480219	5	14	71		1	1
8140811630160	3221910480264	6.3	16	71		1	1
8140811600180	3221910480257	6	18	80		1	1
8140811800200	3221910480271	8	20	80		1	1