

High performance milling cutter for grooving thin webs. SLIDECUT coating allows better chip evacuation and a reduction in the coefficient of friction. Made in France.



- Excellent surface finish
- Optimal chip removal
- Superior long life
- Made in France

- Monobloc carbide + PVD
- SLIDECUT coating

Machine



Application



Features



Properties and benefits

- + Monobloc carbide + PVD : Tool body made of solid tungsten carbide (HM) with a PVD coating. ➡ Allows for better chip evacuation. Extends tool life and optimises cutting conditions.
- + SLIDECUT coating : Hardness 4000HV, coefficient of friction 0,15, resistance to heat (950°C). ➡ Very high hardness. Low friction coefficient. Excellent chip evacuation.



| Item number M3 | EAN (13 digits) | M3 | Cutter diameter | Handle diameter or CM | Total length | Trimmed length | Number of teeth |
|----------------|-----------------|----|-----------------|-----------------------|--------------|----------------|-----------------|
| 82362510300 | 3221910830083 | | 3 | 6 | 8 | 57 | |
| 82362510400 | 3221910830090 | | 4 | 6 | 11 | 57 | |
| 82362510500 | 3221910830106 | | 5 | 6 | 13 | 57 | |
| 82362510600 | 3221910830113 | | 6 | 6 | 13 | 57 | |
| 82362510800 | 3221910830120 | | 8 | 8 | 19 | 63 | |
| 82362511000 | 3221910830137 | | 10 | 10 | 22 | 72 | |
| 82362511200 | 3221910830144 | | 12 | 12 | 26 | 83 | |
| 82362511400 | 3221910830151 | | 14 | 14 | 26 | 83 | |
| 82362511600 | 3221910830168 | | 16 | 16 | 32 | 92 | |
| 82362511800 | 3221910830175 | | 18 | 18 | 32 | 92 | |
| 82362512000 | 3221910830182 | | 20 | 20 | 38 | 104 | |