

Manual tapping of steels and stainless steels.



- Especially for high-strength steels, stainless steels and cast irons
- Especially for stainless steels

Machine



Application

M 1	M 2	P
M1 - austenitic stainless steels	M2- Super austenitic stainless steels	P- Ferrous Long Chip Steels

Features

M	6H		HSS-E PM	BRIGHT UNCOATED	ISO 529	CYL+	X3 SET
----------	-----------	--	---------------------	----------------------------	--------------------	-------------	-------------------



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
950103100300050	8420609240348	M 3	3	0,5	ISO 529	2,50	48	11		2,50	3	1
950103100400070	8420609240362	M 4	4	0,7	ISO 529	3,30	53	13		3,15	3	1
950103100500080	8420609240379	M 5	5	0,8	ISO 529	4,20	58	16		4,00	3	1
950103100600100	8420609240386	M 6	6	1	ISO 529	5,00	66	19		5,00	3	1
950103100800125	8420609240409	M 8	8	1,25	ISO 529	6,75	72	22		6,30	3	1
950103101000150	8420609240430	M 10	10	1,5	ISO 529	8,50	80	24		8,00	3	1
950103101200175	8420609240447	M 12	12	1,75	ISO 529	10,25	89	29		7,10	3	1
950103101400200	8420609240454	M 14	14	2	ISO 529	12,00	95	30		9,00	3	1
950103101600200	8420609240461	M 16	16	2	ISO 529	14,00	102	32		10,00	3	1