

9501081 | Set of 3 Standard left-hand taps HSS -M -DIN 352 -Stepped profile -6H

Manual tapping of steels.




- Threading of standard Steels
- Gradual work
- Made in Spain
- High-speed steel

Machine



Application



Features



Properties and benefits

+ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
950108100400070	8420609241192	M	4	0,7	DIN 352	3,30	45	13	2 > 8.5	3,40	3	1
950108100500080	8420609241208	M	5	0,8	DIN 352	4,20	50	15	2 > 8.5	4,90	3	1
950108100600100	8420609241215	M	6	1	DIN 352	5,00	50	16	2 > 8.5	4,90	3	1
950108100800125	8420609241239	M	8	1,25	DIN 352	6,75	56	22	2 > 8.5	6,20	3	1
950108101000150	8420609241253	M	10	1,5	DIN 352	8,50	70	24	2 > 8.5	5,50	3	1
950108101200175	8420609241277	M	12	1,75	DIN 352	10,25	75	29	2 > 8.5	7,00	3	1
950108101400200	8420609241284	M	14	2	DIN 352	12,00	80	30	2 > 8.5	9,00	3	1
950108101600200	8420609241291	M	16	2	DIN 352	14,00	80	32	2 > 8.5	9,00	3	1