

Manual tapping of steels.




- Threading of standard Steels
- Gradual work
- Made in Spain
- High-speed steel

### Machine



### Application



### Features



### Properties and benefits

+ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm<sup>2</sup>



| Code            | EAN           | Thread | Ø     | Pitch | Norm    | Drill | L   | I  | I4      | I5    | QTY | PCB |
|-----------------|---------------|--------|-------|-------|---------|-------|-----|----|---------|-------|-----|-----|
| 951101100180400 | 8420609247828 | BSW    | 1/8"  | 40    | DIN 352 | 2,55  | 40  | 11 | 2 > 8,5 | 2,70  | 3   | 1   |
| 951101100532320 | 8420609247880 | BSW    | 5/32" | 32    | DIN 352 | 3,20  | 45  | 13 | 2 > 8,5 | 3,40  | 3   | 1   |
| 951101100316240 | 8420609247835 | BSW    | 3/16" | 24    | DIN 352 | 3,70  | 50  | 16 | 2 > 8,5 | 4,90  | 3   | 1   |
| 951101100732240 | 8420609247910 | BSW    | 7/32" | 24    | DIN 352 | 4,50  | 50  | 18 | 2 > 8,5 | 4,90  | 3   | 1   |
| 951101100140200 | 8420609247811 | BSW    | 1/4"  | 20    | DIN 352 | 5,10  | 56  | 22 | 2 > 8,5 | 4,90  | 3   | 1   |
| 951101100516180 | 8420609247873 | BSW    | 5/16" | 18    | DIN 352 | 6,50  | 63  | 25 | 2 > 8,5 | 4,90  | 3   | 1   |
| 951101100380160 | 8420609247866 | BSW    | 3/8"  | 16    | DIN 352 | 7,90  | 70  | 28 | 2 > 8,5 | 5,50  | 3   | 1   |
| 951101100716140 | 8420609247903 | BSW    | 7/16" | 14    | DIN 352 | 9,25  | 75  | 30 | 2 > 8,5 | 6,20  | 3   | 1   |
| 951101100120120 | 8420609247804 | BSW    | 1/2"  | 12    | DIN 352 | 10,50 | 80  | 32 | 2 > 8,5 | 7,00  | 3   | 1   |
| 951101100916120 | 8420609247934 | BSW    | 9/16" | 12    | DIN 352 | 12,00 | 80  | 32 | 2 > 8,5 | 9,00  | 3   | 1   |
| 951101100580110 | 8420609247897 | BSW    | 5/8"  | 11    | DIN 352 | 10,50 | 90  | 36 | 2 > 8,5 | 7,00  | 3   | 1   |
| 951101100340100 | 8420609247859 | BSW    | 3/4"  | 10    | DIN 352 | 16,50 | 105 | 40 | 2 > 8,5 | 11,00 | 3   | 1   |
| 951101100780090 | 8420609247927 | BSW    | 7/8"  | 9     | DIN 352 | 19,25 | 110 | 45 | 2 > 8,5 | 14,50 | 3   | 1   |
| 951101110000080 | 8420609247958 | BSW    | 1"    | 8     | DIN 352 | 22,00 | 110 | 50 | 2 > 8,5 | 16,00 | 3   | 1   |
| 951101110140070 | 8420609247972 | BSW    | 1"1/4 | 7     | DIN 352 | 27,75 | 125 | 56 | 2 > 8,5 | 20,00 | 3   | 1   |