

Manual tapping of steels.



- Threading of standard Steels
- Gradual work
- High-speed steel

Machine



Application

P
1

P1-
Unrealized
steels

P
2

P2-
Weakly
allied
steels

P
3

P3- strong
alloy steels

Features

BSW

HSS

BRIGHT
UNCOATED

DIN
352

CYL+

X3
SET

Properties and benefits

+ High-speed steel: HSS substrate → For general use in steels and cast irons up to 950 N/mm²



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
951101100180400	8420609247828	BSW 1/8"	40	DIN 352	2,55	40	11	2 > 8.5	2,70	3	1	
951101100532320	8420609247880	BSW 5/32"	32	DIN 352	3,20	45	13	2 > 8.5	3,40	3	1	
951101100316240	8420609247835	BSW 3/16"	24	DIN 352	3,70	50	16	2 > 8.5	4,90	3	1	
951101100732240	8420609247910	BSW 7/32"	24	DIN 352	4,50	50	18	2 > 8.5	4,90	3	1	
951101100140200	8420609247811	BSW 1/4"	20	DIN 352	5,10	56	22	2 > 8.5	4,90	3	1	
951101100516180	8420609247873	BSW 5/16"	18	DIN 352	6,50	63	25	2 > 8.5	4,90	3	1	
951101100380160	8420609247866	BSW 3/8"	16	DIN 352	7,90	70	28	2 > 8.5	5,50	3	1	
951101100716140	8420609247903	BSW 7/16"	14	DIN 352	9,25	75	30	2 > 8.5	6,20	3	1	
951101100120120	8420609247804	BSW 1/2"	12	DIN 352	10,50	80	32	2 > 8.5	7,00	3	1	
951101100916120	8420609247934	BSW 9/16"	12	DIN 352	12,00	80	32	2 > 8.5	9,00	3	1	
951101100580110	8420609247897	BSW 5/8"	11	DIN 352	10,50	90	36	2 > 8.5	7,00	3	1	
951101100340100	8420609247859	BSW 3/4"	10	DIN 352	16,50	105	40	2 > 8.5	11,00	3	1	
951101100780090	8420609247927	BSW 7/8"	9	DIN 352	19,25	110	45	2 > 8.5	14,50	3	1	
951101110000080	8420609247958	BSW 1"	8	DIN 352	22,00	110	50	2 > 8.5	16,00	3	1	
951101110140070	8420609247972	BSW 1 1/4"	7	DIN 352	27,75	125	56	2 > 8.5	20,00	3	1	