

Manual tapping of steels.




- Especially for high-strength steels and cast irons
- Comfort and precision
- Gradual work
- Made in Spain
- High-speed steel

Machine



Application



Features



Properties and benefits

+ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
951102100140260	8420609248061	BSF	1/4"	26	DIN 2181	5,30	56	22	2 > 6.5	4,90	2	1
951102100380200	8420609248092	BSF	3/8"	20	DIN 2181	8,30	70	28	2 > 6.5	5,50	2	1
951102100716180	8420609248122	BSF	7/16"	18	DIN 2181	9,70	75	30	2 > 6.5	6,20	2	1
951102100120160	8420609248054	BSF	1/2"	16	DIN 2181	11,10	80	32	2 > 6.5	7,00	2	1
951102100916160	8420609248146	BSF	9/16"	16	DIN 2181	12,70	80	32	2 > 6.5	9,00	2	1
951102100780110	8420609248139	BSF	7/8"	19,5	DIN 2181	19,75	45	18	2 > 6.5	14,50	2	1
951102110000100	8420609248153	BSF	1"	10	DIN 2181	22,75	110	50	2 > 6.5	16,00	2	1