

Manual tapping of steels.



- Threading of standard Steels
- Gradual work
- High-speed steel

Machine



Application



Features



Properties and benefits

+ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
952101100002560	8420609249839	UNC N°2	56	DIN 352	1,90	36	10	2 > 8.5			3	1
952101100004400	8420609249853	UNC N°4	40	DIN 352	2,30	40	11	2 > 8.5	2,70		3	1
952101100005400	8420609249860	UNC N°5	40	DIN 352	2,60	40	11	2 > 8.5	2,70		3	1
952101100006320	8420609249877	UNC N°6	32	DIN 352	2,85	45	13	2 > 8.5	3,00		3	1
952101100008320	8420609249884	UNC N°8	32	DIN 352	3,50	45	13	2 > 8.5	3,40		3	1
952101100010240	8420609249891	UNC N°10	24	DIN 352	3,90	50	16	2 > 8.5	4,90		3	1
952101100012240	8420609249907	UNC N°12	24	DIN 352	4,50	50	18	2 > 8.5	4,90		3	1
952101100140200	8420609249921	UNC 1/4"	20	DIN 352	5,10	56	22	2 > 8.5	4,90		3	1
952101100516180	8420609249976	UNC 5/16"	18	DIN 352	6,50	63	25	2 > 8.5	4,90		3	1
952101100380160	8420609249952	UNC 3/8"	16	DIN 352	7,90	70	28	2 > 8.5	5,50		3	1
952101100716140	8420609249990	UNC 7/16"	14	DIN 352	9,25	75	30	2 > 8.5	6,20		3	1
952101100120130	8420609249914	UNC 1/2"	13	DIN 352	10,50	80	32	2 > 8.5	7,00		3	1
952101100916120	8420609250019	UNC 9/16"	12	DIN 352	12,00	80	32	2 > 8.5	9,00		3	1
952101100580110	8420609249983	UNC 5/8"	11	DIN 352	13,50	90	36	2 > 8.5	9,00		3	1
952101100340100	8420609249945	UNC 3/4"	10	DIN 352	16,50	105	40	2 > 8.5	11,00		3	1
952101100780090	8420609250002	UNC 7/8"	9	DIN 352	19,25	110	45	2 > 8.5	14,50		3	1
952101110000080	8420609250026	UNC 1"	8	DIN 352	22,00	110	50	2 > 8.5	16,00		3	1