

# 9600021 | Standard "left" machine tap HSS-E5 (cobalt 5%) -M -DIN 371 -B Shape (GUN) -6H

Tap for steel, stainless steel and aluminium. Particularly suitable for through tapping thanks to its Gun entry.



- Left Thread
- Threading of standard Steels
- Made in Spain
- GUN entry
- 5% cobalt HSS

## Machine



## Application



P1-  
Unrealized  
steels

P2-  
Weakly  
allied  
steels

## Features



## Properties and benefits

- + Gun entry: entry geometry consisting of facets shaped to guide debris towards the front. Improves threading efficiency and precision. ➡ Enables the clearance of debris towards the front, for the simple and precise tapping of through-holes.
- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➡ For general use in metals up to 1200 N/mm².



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960002100300050	3221912241382	M 3	0.5	DIN 371	2,50	56	10	4-4.5	2,70	1	1	
960002100400070	3221912241399	M 4	0.7	DIN 371	3,30	63	12	4-4.5	3,40	1	1	
960002100500080	3221912241405	M 5	0.8	DIN 371	4,20	70	12	4-4.5	4,90	1	1	
960002100600100	3221912241412	M 6	1	DIN 371	5,00	80	15	4-4.5	4,90	1	1	
960002100800125	3221912241429	M 8	1.25	DIN 371	6,75	90	18	4-4.5	6,20	1	1	
960002101000150	3221912241436	M 10	1.5	DIN 371	8,50	100	22	4-4.5	8,00	1	1	