


**9600121 | Standard "LEFT" machine tap HSS-E5 (cobalt 5%) -M -DIN 376 -B Shape (GUN) -6H**

Tap for steel, stainless steel and aluminium. Particularly suitable for through tapping thanks to its Gun entry.



- Left Thread
- Threading of standard Steels
  
- GUN entry
- 5% cobalt HSS

**Machine**



**Application**

<b>N</b> 1.4.1	<b>N</b> 1.4.2	<b>P</b> 1	<b>P</b> 2	<b>P</b> 3	<b>P</b> 5
N1-4-1- Aluminum-based alloy-4000 series: Silicon	N1-4-2-- Aluminum Alloy- Series: 4000: 0,5%	P1- Unrealized steels	P2- Weakly allied steels	P3- strong alloy steels	P5- Ferritic stainless steels

**Features**



**Properties and benefits**

- + Gun entry: entry geometry consisting of facets shaped to guide debris towards the front. Improves threading efficiency and precision. ↻ Enables the clearance of debris towards the front, for the simple and precise tapping of through-holes.
- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ↻ For general use in metals up to 1200 N/mm<sup>2</sup>.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960012101200175	3221912241443	M	12	1.75	DIN 376	10,25	110	22	4-4.5	7,00	1	1