

**9603121 | Machine tap HSS-E5 (cobalt 5%) -M -DIN 376 -B
Shape (GUN) -4H**

Tap for steel, stainless steel and aluminium. Particularly suitable for through tapping thanks to its Gun entry.



- **Precise thread tapping**
- **Threading of standard Steels**

- **GUN entry**
- **5% cobalt HSS**

Machine



Application

N 1.4.1	N 1.4.2	P 1	P 2	P 3	P 5
N1-4-1- Aluminum-based alloy-4000 series: Silicon	N1-4-2-- Aluminum Alloy- Series: 4000: 0,5%	P1- Unrealized steels	P2- Weakly allied steels	P3- strong alloy steels	P5- Ferritic stainless steels

Features

M	4H	FORM B GUN	 GUN	HSS E5	BRIGHT UNCOATED	DIN 376	CYL+ <input type="checkbox"/>	 4-4 H5
----------	-----------	----------------------	---------	---------------	------------------------	----------------	--------------------------------------	------------

Properties and benefits

- + Gun entry: entry geometry consisting of facets shaped to guide debris towards the front. Improves threading efficiency and precision. ↻ Enables the clearance of debris towards the front, for the simple and precise tapping of through-holes.
- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ↻ For general use in metals up to 1200 N/mm².



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960312101200175	3221912240842	M	12	1.75	DIN 376	10,25	110	22	4-4.5	7,00	1	1