




- Threading of standard Steels
- Spiral flute
- 5% cobalt HSS

**Machine**



**Application**

<b>N</b> 1.4.1	<b>N</b> 1.4.2	<b>P</b> 1	<b>P</b> 2	<b>P</b> 3	<b>P</b> 5
N1-4-1- Aluminum-based alloy-4000 series: Silicon	N1-4-2-- Aluminum Alloy- Series: 4000: 0,5%	P1- Unrealized steels	P2- Weakly allied steels	P3- strong alloy steels	P5- Ferritic stainless steels

**Features**

<b>M</b>	<b>6G</b>	<b>FORM C</b>	<b>35°</b>	<b>HSS E5</b>	<b>BRIGHT UNCOATED</b>	<b>DIN 376</b>	<b>CYL+</b>	<b>2-3 Hls</b>
----------	-----------	---------------	------------	---------------	------------------------	----------------	-------------	----------------

**Properties and benefits**

- + Spiral flute : A flute shape that allows chips to be evacuated through the entrance to the hole. → Allows better heat resistance due to better chip evacuation. For blind holes.
- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) → For general use in metals up to 1200 N/mm<sup>2</sup>.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960325101200175	8420609313165	M	12	1.75	DIN 376	10,25	110	16	2-3	7,00	1	1