

Tap (sintered steel) for cast iron. Reinforced tail.



- Especially for cast irons
- STEAM treatment

Machine



Application

K
1

K1-
Malleable
Cast iron

K
2

K2- Gray
Cast iron

K
3

K3-
Nodular
and GS
Cast iron

Features

M
MF

6H

FORM
C

HSS-E
PM

STEAM
NIT
TREATED

DIN
371

CYL+

Properties and benefits

- +
- STEAM treatment : Steam oxidation treatment. → Avoids cold bonding. Reduced coefficient of friction in steels.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960541100300050	8420609320767	M	3	0,5	DIN 371	2,50	56	10	2-3	2,70	1	1
960541100350060	8420609320774	M	3.5	0,6	DIN 371	2,90	56	11	2-3	3,00	1	1
960541100400070	8420609320781	M	4	0,7	DIN 371	3,30	63	12	2-3	3,40	1	1
960541100500080	8420609320804	M	5	0,8	DIN 371	4,20	70	14	2-3	4,90	1	1
960541100600100	8420609320811	M	6	1	DIN 371	5,00	80	16	2-3	4,90	1	1
960541100800125	8420609320842	M	8	1,25	DIN 371	6,75	90	18	2-3	6,20	1	1
960541101000150	8420609320880	M	10	1,5	DIN 371	8,50	100	20	2-3	8,00	1	1
960541100800100	8420609320835	MF	8	1	DIN 371	7,00	90	18	2-3	6,20	1	1