

**9606021 | Machine tap HSSE-PM -M MF -DIN 374/376 -B  
Shape (GUN) -6H -Dulofix shank**

Tap (sintered steel) for steels. Particularly suitable for through tapping thanks to its Gun entry.




- Especially for high-strength steels, stainless steels and cast irons
- GUN entry

**Machine**



**Application**



**Features**



**Properties and benefits**

- + Gun entry: entry geometry consisting of facets shaped to guide debris towards the front. Improves threading efficiency and precision. ➔ Enables the clearance of debris towards the front, for the simple and precise tapping of through-holes.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960602100400070	8420609323515	M	4	0,7	DIN 376	3,30	63	12	4-4.5	2,10	1	1
960602100500080	8420609323522	M	5	0,8	DIN 376	4,20	70	14	4-4.5	2,70	1	1
960602100600100	8420609323539	M	6	1	DIN 376	5,00	80	16	4-4.5	3,40	1	1
960602100800125	8420609323560	M	8	1,25	DIN 376	6,75	90	18	4-4.5	4,90	1	1
960602101000150	8420609323607	M	10	1,5	DIN 376	8,50	100	20	4-4.5	5,50	1	1
960602101200175	8420609323652	M	12	1,75	DIN 376	10,25	110	22	4-4.5	7,00	1	1
960602101400200	8420609323683	M	14	2	DIN 376	12,00	110	25	4-4.5	9,00	1	1
960602101600200	8420609323713	M	16	2	DIN 376	14,00	110	28	4-4.5	9,00	1	1
960602101800250	8420609323737	M	18	2,5	DIN 376	15,50	125	32	4-4.5	11,00	1	1
960602100800100	8420609323553	MF	8	1	DIN 374	7,00	90	18	4-4.5	4,90	1	1
960602101000100	8420609323584	MF	10	1	DIN 374	9,00	90	18	4-4.5	5,50	1	1
960602101200150	8420609323645	MF	12	1,5	DIN 374	10,50	100	22	4-4.5	7,00	1	1
960602101400150	8420609323676	MF	14	1,5	DIN 374	12,50	100	22	4-4.5	9,00	1	1
960602101800150	8420609558221	MF	18	1,5	DIN 374	16,50	110	25	4-4.5	11,00	1	1