

Tap (sintered steel) for cast iron. Passing tail.




- Especially for cast irons
- Precise and long-lasting thread tapping
- Superior long life
- Made in Spain
- STEAM treatment

Machine



Application



Features



Properties and benefits

- + STEAM treatment : Steam oxidation treatment. ➡ Avoids cold bonding. Reduced coefficient of friction in steels.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960641100600100	8420609326981	M	6	1	DIN 376	5,00	80	16	2-3	3,40	1	1
960641100800125	8420609327025	M	8	1,25	DIN 376	6,75	90	18	2-3	4,90	1	1
960641101000150	8420609327063	M	10	1,5	DIN 376	8,50	100	20	2-3	5,50	1	1
960641101200175	8420609327117	M	12	1,75	DIN 376	10,25	110	22	2-3	7,00	1	1
960641101400200	8420609327131	M	14	2	DIN 376	12,00	110	25	2-3	9,00	1	1
960641101600200	8420609327155	M	16	2	DIN 376	14,00	110	28	2-3	9,00	1	1
960641100800100	8420609327018	MF	8	1	DIN 374	7,00	90	18	2-3	4,90	1	1
960641101000100	8420609327049	MF	10	1	DIN 374	9,00	90	18	2-3	5,50	1	1
960641101200150	8420609327100	MF	12	1,5	DIN 374	10,50	100	22	2-3	7,00	1	1
960641101400150	8420609327124	MF	14	1,5	DIN 374	12,50	100	22	2-3	9,00	1	1
960641101600150	8420609327148	MF	16	1,5	DIN 374	14,50	110	22	2-3	9,00	1	1