

9606411 | Standard machine tap HSSE-PM -STEAM treatment -MMF -DIN 374/376 -6H -Straight -Dulofix shank

Tap (sintered steel) for cast iron. Passing tail.



- Especially for cast irons
- STEAM treatment

Machine



Application

K
1

K1-
Malleable
Cast iron

K
2

K2- Gray
Cast iron

K
3

K3-
Nodular
and GS
Cast iron

Features

M
MF

6H

FORM
C

HSS-E
PM

STEAM
NIT
TREATED

DIN
374/376

Properties and benefits

- + STEAM treatment : Steam oxidation treatment. ➡ Avoids cold bonding. Reduced coefficient of friction in steels.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960641100600100	8420609326981	M 6	6	1	DIN 376	5,00	80	16	2-3	3,40	1	1
960641100800125	8420609327025	M 8	8	1,25	DIN 376	6,75	90	18	2-3	4,90	1	1
960641101200175	8420609327117	M 12	12	1,75	DIN 376	10,25	110	22	2-3	7,00	1	1
960641101400200	8420609327131	M 14	14	2	DIN 376	12,00	110	25	2-3	9,00	1	1