

**960ASG1 | Multi-application machine tap HSSE-PM -CrN PLUS coated -M -DIN 371/376 -Thread-former -6GX**

"By deformation" tap (sintered steel) for aluminium alloys. CrN PLUS coating provides improved heat resistance and a reduced coefficient of friction.



- Especially for aluminium
- Precise thread tapping
- Made in Spain

**Machine**



**Application**



N- Non-ferrous alloys

**Features**



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960ASG100300050	3221912217042	M 3	0.5	DIN 371	2,80	56	10	2-2.5	2,70	1	1	
960ASG100400070	3221912217059	M 4	0.7	DIN 371	3,70	63	12	2-2.5	3,40	1	1	
960ASG100500080	3221912217066	M 5	0.8	DIN 371	4,65	70	12	2-2.5	4,90	1	1	
960ASG100600100	3221912217073	M 6	1	DIN 371	5,60	80	15	2-2.5	4,90	1	1	
960ASG100800125	3221912217080	M 8	1.25	DIN 371	7,40	90	18	2-2.5	6,20	1	1	
960ASG101000150	3221912217097	M 10	1.5	DIN 371	9,30	100	22	2-2.5	8,00	1	1	
960ASG101200175	3221912217103	M 12	1.75	DIN 376	11,20	110	22	2-2.5	7,00	1	1	