

960SRH1 | Multi-application machine tap HSSE-PM -TIN 20 coated -M MF -DIN 371/374/376 -Thread-former -6HX -Grooved

"By deformation" tap (sintered steel) for steels, stainless steels and cast iron. TiN 20 coating gives it an increased service life and high resistance to abrasion.



- Especially for high-strength steels, stainless steels and cast irons
- Precise thread tapping
- TiN20 coating

Machine



Application



K3-
Nodular
and GS
Cast iron

P- Ferrous
Long Chip
Steels

Features



Properties and benefits

- + TiN20 coating : Hardness 2300HV, coefficient of friction 0,60, resistance to heat (600°C). ↻ Very high abrasion resistance. Increased tool life.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960SRH100300050	3221912216687	M	3	0.5	DIN 371	2,80	56	10	2-2.5	2,70	1	1
960SRH100400070	3221912216700	M	4	0.7	DIN 371	3,70	63	12	2-2.5	3,40	1	1
960SRH100500080	3221912216717	M	5	0.8	DIN 371	4,65	70	12	2-2.5	4,90	1	1
960SRH100600100	3221912216724	M	6	1	DIN 371	5,60	80	15	2-2.5	4,90	1	1
960SRH100800100	3221912216731	MF	8	1	DIN 371	7,50	90	18	2-2.5	6,20	1	1
960SRH100800125	3221912216748	M	8	1.25	DIN 371	7,40	90	18	2-2.5	6,20	1	1
960SRH101000100	3221912216755	MF	10	1	DIN 371	9,50	90	18	2-2.5	8,00	1	1
960SRH101000150	3221912216762	M	10	1.5	DIN 371	9,30	100	22	2-2.5	8,00	1	1
960SRH101200150	3221912216779	MF	12	1.5	DIN 374	11,30	100	22	2-2.5	7,00	1	1
960SRH101200175	3221912216786	M	12	1.75	DIN 376	11,20	110	22	2-2.5	7,00	1	1
960SRH101400150	3221912216793	MF	14	1.5	DIN 374	13,30	100	22	2-2.5	9,00	1	1
960SRH101400200	3221912216809	M	14	2	DIN 376	13,00	110	25	2-2.5	9,00	1	1
960SRH101600200	3221912216816	M	16	2	DIN 376	15,00	110	28	2-2.5	9,00	1	1