

Tap for short-chipping metals. Reinforced tail. Profile: UNC UNF.




- Especially for steels and cast irons
- Precise thread tapping
- Made in Spain
- 5% cobalt HSS

## Machine



## Application



## Features



## Properties and benefits

- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➡ For general use in metals up to 1200 N/mm².



| Code            | EAN           | Thread | Ø     | Pitch | Norm    | Drill | L   | I  | I4  | I5   | QTY | PCB |
|-----------------|---------------|--------|-------|-------|---------|-------|-----|----|-----|------|-----|-----|
| 962201100006320 | 8420609340314 | UNC    | N°6   | 32    | DIN 371 | 2,85  | 56  | 11 | 2-3 | 3,00 | 1   | 1   |
| 962201100008320 | 8420609340338 | UNC    | N°8   | 32    | DIN 371 | 3,50  | 63  | 12 | 2-3 | 3,40 | 1   | 1   |
| 962201100140200 | 8420609340406 | UNC    | 1/4"  | 20    | DIN 371 | 5,10  | 80  | 16 | 2-3 | 5,50 | 1   | 1   |
| 962201100380160 | 8420609340420 | UNC    | 3/8"  | 16    | DIN 371 | 7,90  | 90  | 18 | 2-3 | 7,00 | 1   | 1   |
| 962201100516180 | 8420609340444 | UNC    | 5/16" | 18    | DIN 371 | 6,50  | 90  | 18 | 2-3 | 6,20 | 1   | 1   |
| 962201100010320 | 8420609340369 | UNF    | N°10  | 32    | DIN 371 | 4,10  | 70  | 14 | 2-3 | 4,90 | 1   | 1   |
| 962201100140280 | 8420609340413 | UNF    | 1/4"  | 28    | DIN 371 | 5,50  | 80  | 16 | 2-3 | 5,50 | 1   | 1   |
| 962201100380240 | 8420609340437 | UNF    | 3/8"  | 24    | DIN 371 | 8,50  | 100 | 18 | 2-3 | 7,00 | 1   | 1   |