

Tap for short-chipping metals. Passing tail. Profile: UNC.



- Especially for high-strength steels, stainless steels and cast irons
- 5% cobalt HSS

**Machine**



**Application**

<b>P1</b>	<b>P2</b>	<b>P3</b>
P1- Unrealized steels	P2- Weakly allied steels	P3- strong alloy steels

**Features**

<b>UNF</b>	<b>2B</b>	<b>FORM C</b>		<b>HSS E5</b>	<b>BRIGHT UNCOATED</b>	<b>DIN 376</b>	<b>CYL+</b>	
------------	-----------	---------------	--	---------------	------------------------	----------------	-------------	--

**Properties and benefits**

- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) → For general use in metals up to 1200 N/mm<sup>2</sup>.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
962301100716200	8420609342578	UNF	7/16"	20	DIN 376	9,90	100	22	2-3	6,20	1	1
962301100120200	8420609342455	UNF	1/2"	20	DIN 376	11,50	110	25	2-3	7,00	1	1
962301100916180	8420609342615	UNF	9/16"	18	DIN 376	12,90	110	25	2-3	9,00	1	1
962301100340160	8420609342493	UNF	3/4"	16	DIN 376	17,50	125	32	2-3	11,00	1	1