962BT11 | Flashcut machine tap HSS-E5 (cobalt 5%) -UNC UNF -DIN 371/374/376 -Straight -2B

High performance tap for brass and copper alloys. Profile: UNC UNF.





- **Precise and long-lasting thread tapping**
- **Superior long life**
- **Made in Spain**

- 5% cobalt HSS

Machine



Application



N3-2- Copper-brass alloy with pb ≤ 1%

N3-4- Copper-Bronze Alloy

O1- Thermoplastics

Features



Properties and benefits

✚ 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➔ For general use in metals up to 1200 N/mm².



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	l	l4	l5	QTY	PCB
962BT1100140200	8420609614941	UNC	1/4"	20	DIN 371	5,10	80	16	2-3	5,50	1	1
962BT1100380160	8420609614989	UNC	3/8"	16	DIN 371	7,90	90	18	2-3	7,00	1	1
962BT1100120130	8420609614927	UNC	1/2"	13	DIN 376	10,50	110	25	2-3	6,20	1	1
962BT1100340100	8420609614965	UNC	3/4"	10	DIN 376	16,50	125	32	2-3	11,00	1	1
962BT1110000080	8420609615009	UNC	1"	8	DIN 376	22,00	160	36	2-3	16,00	1	1
962BT1100140280	8420609614958	UNF	1/4"	28	DIN 371	5,50	80	16	2-3	4,90	1	1
962BT1100380240	8420609614996	UNF	3/8"	24	DIN 371	8,50	100	18	2-3	5,50	1	1
962BT1100120200	8420609614934	UNF	1/2"	20	DIN 376	11,50	110	25	2-3	7,00	1	1
962BT1100340160	8420609614972	UNF	3/4"	16	DIN 376	17,50	125	32	2-3	11,00	1	1
962BT1110000120	8420609615016	UNF	1"	12	DIN 376	23,25	140	32	2-3	16,00	1	1