


Metal tapping with short chips.



- Especially for high-strength steels, stainless steels and cast irons
- High-speed steel

**Machine**



**Application**

<b>N</b> 1.4.1	<b>N</b> 1.4.2	<b>P</b> 1	<b>P</b> 2	<b>P</b> 3	<b>P</b> 5
N1-4-1- Aluminum-based alloy-4000 series: Silicon	N1-4-2-- Aluminum Alloy- Series: 4000: 0,5%	P1- Unrealized steels	P2- Weakly allied steels	P3- strong alloy steels	P5- Ferritic stainless steels

**Features**



**Properties and benefits**

+ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm<sup>2</sup>



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
964310100116270	8420609351143	NPT	1/16"	27	TivolyNorm	56	15	2-3			1	1
964310100180270	8420609351174	NPT	1/8"	27	TivolyNorm	70	15	2-3	6,20		1	1
964310100140180	8420609351167	NPT	1/4"	18	TivolyNorm	70	21	2-3	9,00		1	1
964310100380180	8420609351198	NPT	3/8"	18	TivolyNorm	75	21	2-3	11,00		1	1
964310100120140	8420609351150	NPT	1/2"	14	TivolyNorm	80	27	2-3	14,50		1	1
964310100340140	8420609351181	NPT	3/4"	14	TivolyNorm	90	27	2-3	18,00		1	1
964310110000115	8420609351211	NPT	1"	11,5	TivolyNorm	110	33	2-3	20,00		1	1