

Alésoir à main HSS expansible. Queue cylindrique avec carré d'entraînement.




■ Usage polyvalent

■ Acier rapide

Machines



Applications



Caractéristiques



Propriétés et bénéfices

+ Acier rapide : Substrat HSS ➡ Pour les usages généraux dans l'acier jusqu'à 950 N/mm², les fontes et les aluminiums.



Code	EAN	Ø	d2	L	I	I3	QTY	PCB
10401010500	3221910643553	5	5	85	32		1	1
10401010550	3221910643560	5,5	5,5	85	32		1	1
10401010600	3221910643577	6	6	90	32		1	1
10401010650	3221910643584	6,5	6,5	100	37		1	1
10401010700	3221910643591	7	7	100	37		1	1
10401010750	3221910643607	7,5	7,5	110	42		1	1
10401010800	3221910643614	8	8	110	42		1	1
10401010850	3221910643621	8,5	8,5	120	47		1	1
10401010900	3221910643638	9	9	120	47		1	1
10401010950	3221910643645	9,5	9,5	130	49		1	1
10401011000	3221910643652	10	10	130	49		1	1
10401011050	3221910643669	10,5	10,5	140	54		1	1
10401011100	3221910643676	11	11	140	54		1	1
10401011150	3221910643683	11,5	11,5	150	59		1	1
10401011200	3221910643690	12	12	150	59		1	1
10401011250	3221910643706	12,5	12,5	160	60		1	1
10401011300	3221910643713	13	13	160	60		1	1
10401011350	3221910643720	13,5	13,5	170	65		1	1
10401011400	3221910643737	14	14	170	65		1	1
10401011450	3221910643744	14,5	14,5	180	70		1	1
10401011500	3221910643751	15	15	180	70		1	1
10401011550	3221910643768	15,5	15,5	180	75		1	1
10401011600	3221910643775	16	16	185	75		1	1
10401011650	3221910643782	16,5	16,5	190	75		1	1
10401011700	3221910643799	17	17	190	75		1	1
10401011750	3221910643805	17,5	17,5	200	77		1	1

Alésoir à main HSS expansible. Queue cylindrique avec carré d'entrainement.

10401011800	3221910643812	18	18	200	77	1	1
10401011850	3221910643829	18,5	18.5	205	77	1	1
10401011900	3221910643836	19	19	205	77	1	1
10401011950	3221910643843	19,5	19.5	210	82	1	1
10401012000	3221910643850	20	20	210	82	1	1
10401012100	3221910643867	21	21	215	87	1	1
10401012200	3221910643874	22	22	220	87	1	1
10401012300	3221910643881	23	23	230	89	1	1
10401012400	3221910643898	24	24	235	89	1	1
10401012500	3221910643904	25	25	240	94	1	1
10401012600	3221910643911	26	26	245	95	1	1
10401012700	3221910643928	27	27	260	100	1	1
10401012800	3221910643935	28	28	260	100	1	1
10401012900	3221910643942	29	29	270	102	1	1
10401013000	3221910643959	30	30	270	102	1	1
10401013100	3221910643966	31	31	280	107	1	1
10401013200	3221910643973	32	32	280	107	1	1