

Foret à 60° pour centrer. Forme A.



■ Acier rapide

Machines



Applications



Caractéristiques



Propriétés et bénéfices

+ Acier rapide : Substrat HSS ➡ Pour les usages généraux dans l'acier jusqu'à 950 N/mm², les fontes et les aluminiums.



Code	EAN	Ø	d2	L	I	I.u	QTY	PCB
8140811050315	3221910479763	3.15	0.5	25			1	1
8140811063315	3221910479770	3.15	0.63	25			1	1
8140811080315	3221910479794	3.15	0.8	25			1	1
8140811100315	3221910479831	3.15	1	31			1	1
8140811125315	3221910479893	3.15	1.25	31			1	1
8140811100400	3221910479848	4	1	35			1	1
8140811160400	3221910479923	4	1.6	35			1	1
8140811150500	3221910479916	5	1.5	40			1	1
8140811200500	3221910479947	5	2	40			1	1
8140811200600	3221910479954	6	2	45			1	1
8140811250630	3221910479978	6.3	2.5	45			1	1
8140811250800	3221910480004	8	2.5	50			1	1
8140811300800	3221910480035	8	3	50			1	1
8140811315800	3221910480042	8	3.15	50			1	1
8140811300100	3221910480011	10	3	55			1	1
8140811400100	3221910480059	10	4	55			1	1
8140811400120	3221910480103	12	4	63			1	1
8140811500120	3221910480189	12	5	63			1	1
8140811500125	3221910480202	12.5	5	63			1	1
8140811500140	3221910480219	14	5	71			1	1
8140811630160	3221910480264	16	6.3	71			1	1
8140811600180	3221910480257	18	6	80			1	1
8140811800200	3221910480271	20	8	80			1	1